
Suntrack DUO Battery Charger

12 V / 50 A

With our state of the art, easy to use design, this product will offer you reliable service for providing a multi-stage, multi-input battery charger to charge the different types of batteries you have installed in either your home, boats, RV caravan, 4WD or commercial vehicle.

| | WP-SUNTRACK DUO - 50A 60111430 |
|--|---|
| | |
| OUTPUT RATING | |
| Output Current (Maximum) | 50A |
| Output Voltage | 12V Nominal |
| Output Power | 775W |
| CHARGER DC OUTPUT- HOUSE BATTERY (C | SH1) |
| Selectable Battery Type | GEL, AGM, Flooded, Lithium, Program |
| Bulk /Float Voltage Range | |
| GEL: | 14.4 / 13.7 Vdc |
| AGM: | 14.6 / 13.6 Vdc |
| Flooded: | 14.4 / 13.3 Vdc |
| Lithium: | 13.9 - 14.6 Vdc |
| Program: | 13.8 - 14.8 Vdc |
| Restart Voltage (GEL, AGM, Flooded, Program) | 12.5 Vdc |
| Restart Voltage (Lithium) | 13.3 Vdc |
| Charger Current (User Selectable) | 5-50A (5A steps) |
| Equalized Voltage (Flooded Battery only) | 15.5 Vdc |
| Equalized Charging Current | 10% of Bulk Current Setting |
| Charging Control | GEL, AGM Flooded, Program Mode: Two or Three Stages Lithium: Three Stages only |
| DC Output Bank | Single |
| Current draw from CH1 with unit ON | < 70 mA |
| Current draw from CH1 with Unit OFF | < 200 uA |
| Battery Temperature Setting | Low / Normal / High (automatically overridden with optional BTS) |
| Efficiency | 95% |
| Minimum Operating Voltage | 8.0 Vdc |
| DC INPUT - SOLAR ARRAY/PANELS (CH2- S | |
| nput Voltage | 14.5 – 50 Vdc |
| Maximum Solar Input Current | 30A |
| Maximum Solar Input Power: 12V Panel | 500W (600W max) |
| 24V Panel | 750W (800W max) |
| DC INPUT – ALTERNATOR/ START BATTER | , |
| nput Voltage | 10.5 – 16.0 Vdc / 21 – 32 Vdc |
| 1 0 | |
| Maximum Input Current (as per max. setting) | 50A |
| ENVIRONMENTAL AND OPERATING TEMPE | |
| Storage Range | -40° to 158° F |
| Operating Range | -4° to 140° F |
| Humidity | 5-95%, RH non-condensing |
| ngress Protection | IP32 |
| WEIGHT AND DIMENSIONS | 40715-050-077-0041- |
| WP-Suntrack Duo 30/50A | 4.07 lbs, 9.52 x 6.77 x 2.91 in |
| REGULATORY COMPLIANCE | Olean December 1, FOC. 14.FD. LANGUAGE. |
| Standards/EMC (North America) | Class B according to FCC part15B and ANSI C63.4 |
| Standards/EMC (European Union) | CE marked for the EMC directive 2004-108-EC Complying with EN55014-1, EN55014-2, EN61000-3-2 and EN61000-3-3 (as equivalent IEC standards series) |





KrakenPower

Tel: +1 (619) 670-9590 theteam@krakenpower.com

www.krakenpower.com