

# Duct Cuff Ordering Guide

## Hazardous Location & Explosive Atmospheres

Anti-Static Conductive Duct - prevents the buildup of static charges generated by airflow. Air movement causes a static charge through friction. Accumulation of these charges can lead to sparks that may be enough to create serious problems that compromise safety in Hazardous Locations.

The duct comes with an easy-to-carry bag and can be attached to another duct in a quick and easy procedure, without the use of space-consuming adapters, that usually take time to install.

Ducting		
MODEL	PART #	DESCRIPTION
<b>Anti-Static Duct w/Storage Bag</b>		
Duct	FDT-0815CBB	8"/20cm Conductive reinforced duct, 15'/4.6m
Duct	FDT-0825CBB	8"/20cm Conductive reinforced duct, 25'/7.6m
Duct	FDT-1215CBB	12"/30cm Conductive reinforced duct, 15'/4.6m
Duct	FDT-1225CBB	12"/30cm Conductive reinforced duct, 25'/7.6m
Duct	FDT-1615CBR	16"/40cm Conductive reinforced duct, 15'/4.6m
Duct	FDT-1625CBR	16"/40cm Conductive reinforced duct. 25'/7.6m
<b>Disposable Duct</b>		
Duct	FDT-12DISP	12"/30cm Disposable layflat polyethylene duct (4mil)
Duct	FDT-16DISP	16"/40cm Disposable layflat polyethylene duct (4mil)
<b>Layflat Duct</b>		
Duct	FDT-1625SME	16"/40cm Unreinforced layflat duct, 25'/7.6m
Duct	FDT-L4X10SME	16"/40cm 90° Unreinforced duct, 4ft x 10ft

### Anti-Static Duct w/Storage Bag

FDT-	Duct Diameter	Duct Length	Type of Duct	Cuff First End	Cuff Second
Duct	<b>08</b> 8" (20cm)	<b>15</b> 15' (4.6m)	<b>C</b> Conductive	<b>B</b> Belt	<b>B</b> Belt
	<b>12</b> 12" (30cm)	<b>25</b> 25' (7.6m)			<b>R</b> Ring
	<b>16</b> 16" (40cm)				



### Disposable Duct

FDT-	Duct Diameter	Type of Duct
Duct	<b>12</b> 12" (30cm)	<b>DISP</b> Disposable
	<b>16</b> 16" (40cm)	



### Layflat Duct

FDT-	Duct Diameter	Duct Length	Type of Duct
Duct	<b>16</b> 16" (40cm)	<b>25</b> 25' (7.6m)	<b>SME</b> Layflat
	<b>L4</b> 16" (40cm)	<b>X10</b> 4ft x 10ft roll	





### B - Belt

**Standard/Enclosed Belted Cuff** - Creates an easy attachment method or quick connection capability. It includes a belt with a spring clamp that can be cinched around the connection.



### R - Ring

**Ring/Wire Rope** - Keeps the end open for easy airflow; also used for interlocked duct connections; gives the end of the hose form so it won't collapse and make it easier to fit over pipe or ports.

## Replacement Duct for UB20XX Quick Couple Canister

### UB20 ACCESSORIES

ACCESSORIES	PART #	DESCRIPTION
Accessory	EF7004CL	Quick-Couple Canister with 25'(7.6m) of 8"/20cm conductive reinforced duct for UB20XX
Accessory	EF7004CL/DS	Quick-Couple Long Canister, 2 pcs (8"/20cm) conductive duct - 5'/1.5m and 15'/4.6m & duct coupler
Accessory	EF7004CS	Quick-Couple Canister with 15'/4.6m of 8"/20cm conductive reinforced duct for UB20XX

### Replacement duct for UB20XX Quick-Couple Canister

Duct	FDT-0805CCB	8"/20cm Conductive reinforced duct, 5'/1.5m (replacement only)
Duct	FDT-0815CRX	8"/20cm Conductive reinforced duct, 15'/4.6m (replacement only)
Duct	FDT-0825CRX	8"/20cm Conductive reinforced duct, 25'/7.6m (replacement only)



### C - Clamp



### R - Ring



**Replacement Duct for UB20XX Quick-Couple Canister:** a clamp comprising the first cuff end - to adapt to the canister - and a ring on the second cuff end.