

PowerStream

-

FlowPath[™] Control

WORLD'S MOST POWERFUL BATTERY FANS



NEW CATEGORY OF BATTERY-

EX50Li

Model

ber)

Motor

Order #EL5500-2PK

NSN (Nato Stock Num-

Runtime at full speed

Dimensions ($h \times w \times d$)

AMCA Verified Airflow DC Power Supply

AC Power Supply

Battery System

IP Rating

Weight

Approvals

0.9hp 10,120 cfm tested & certified on battery operation



EX50Li 18" (46cm)

4140-01-667-0430

0.9 hp / 0.6 kW

Unlimited (AC)

IP66 / IP66 / IP66

strap (1).

Includes RAMFAN EX50Li 115 VAC (1),

45 minutes (two battery packs)

40V Lithium-ion, 432Wh, 12Ah

22" x 21" x 12" in / 550/530/305 mm with two batteries: 54 lbs / 25 kg

UN 38.3

without batteries: 45 lbs / 20 kg

KC

IEC 62133-2

10,120 cfm (17,194 m³/hr)

9,635 cfm (16,370 m³/hr)

40V 6Ah battery packs (2) and carrying

| P | - | |
|---|----|---------------------|
| 1 | RA | MFAN PowerStream |
| | | |
| 5 | | |




EX50Li

EX1 Urban

| Integrated | |
|--------------------------------|--|
|--------------------------------|--|

- Swappable
- Multi-Missi



EX50Li



POWERED PPV VENTILATORS

EX150Li





50Li Edition


EX150Li All-Terrain Edition

1.9hp 12,377 cfm tested & certified on battery operation





Charger Lithium-Ion Packs on Functionality



| Model | EX150Li 18" (46 cm) | | |
|------------------------|--|---|--|
| Order #EL6500 2PK | Includes RAMFAN EX150Li 52V 8Ah battery (2) , power cord (1), wheel kit assembled (1) | | |
| Motor | 1.9hp / 1.4kw | | |
| Runtime at full speed | 45 minutes (full speed) 30 minutes (MAX mode) Unlimited (AC) | | |
| Input AC | Multiple plug options available | | |
| Battery System | 52V Lithium-Ion, 832Wh, 16Ah | | |
| IP Rating | IP66 / IP66 / IP66 | | |
| Weight | Urban Edition With two batteries: 71 lb (32 kg) With one battery: 64 lb (29 kg) | All-Terrain Edition 77 lb (35 kg) 70 lb (32 kg) | |
| | Without batteries: 58 lb (26 kg) | 63 lb (29 kg) | |
| Dimensions (h x w x d) | 23 x 21 x 19 in 58 x 53 x 48 cm | 23 x 21 x 21 in 58 x 53 x 53 cm | |
| Approvals | UN 38.3 IEC 62133-2 KC | | |
| AMCA Verified Airflow | | | |
| DC Power Supply | 12,377 cfm (21,029 m³/hr) | | |
| AC Power Supply | 11,896 cfm (20,211 m³/hr) | | |

EX150Li



MISSION KITS





PROUDLY MADE IN CALIFORNIA